

JM-240C, HYDRAULIC CRIMPING TOOL

- Hydraulic crimping tool for both copper and aluminium lugs and connectors.
- Selectable crimping die set for a range of lug and connector sizes.
- Choose appropriate die set according to table.
- Light weight due to high quality aluminium housing.
- Automatic retraction when crimping operation is complete.

Crimping force: 100kN
Range: 10mm²-300mm²


Stroke: 16mm
Length: 530mm

Weight: 4kg
Package List:

- JM-240C
- die set
- manual
- plastic carry case



JM-240C

Type	Crimping Shape	Conductor	Crimping Range (mm ²)	Application	Die series
JM-240C		Copper	16-240	JGK, JGY, JGA, JGB, GTY-2	MT
			10-240	GTL(Cu), AUS, GTD, GTLD(Cu)	DT
			10-185	TM	MTA
			35-150	RJ-U, RJ-XAU(Cu)	E
		Aluminium	10-240	CAL-BS, GLM	ML
			16-240	CXAU(AI), RJ-XA, CAL-A	
			25-240	GTL(AI)	
			70-240	RJ-XAU(AI)	
			16-240	ATL, AU, GLI, CAL-BG, GTLZD(AI)	DL
			10-240	GTLD(AI)	MLA
			10-300	CALB-N, MCCB	
			10-120	GTLZ, GTLP	
			4-150	CPTAU, MJPB, MJPT, MJPTN	
			70-120	CAUBT(AI)	E